

Outdoor Furnace Requirements

Non Phase 2 Outdoor Wood Fired Boilers:

1. Non phase 2 outdoor wood fired boilers may be permitted until May 21, 2011.
2. Non phase 2 outdoor wood fired boilers must be installed a minimum of 150 feet from nearest property line.
3. Non phase 2 outdoor wood fired boilers must extend permanently attached stack a minimum of 10 feet above ground and must be installed according to manufacturer's specifications.
4. Non phase 2 outdoor wood fired boilers shall use only allowed fuels, clean wood, wood pallets made from clean wood or home heating oil, natural gas or propane that meets sulfur limits to start or supplement fuel for dual-fired outdoor wood fired boilers.

Phase 2 Outdoor Wood Fired Boilers:

1. Phase 2 outdoor wood fired boilers must be installed a minimum of 50 feet from nearest property line.
2. Phase 2 outdoor wood fired boilers must extend permanently attached stack a minimum of 10 feet above ground and must be installed according to manufacturer's specifications.
3. Phase 2 outdoor wood fired boilers shall use only allowed fuels, clean wood, wood pallets made from clean wood or home heating oil, natural gas or propane that meets sulfur limits to start or supplement fuel for dual-fired outdoor wood fired boilers.

A building permit, mechanical permit and electrical permit are required prior to installation of any outdoor wood fired boiler. Please see permit requirements for further information.